

ÁNGULOS (LADOS IGUALES)

Se manejan en Acero A-572°50 ó A-529°50

ESPESOR	ANCHO	ESPESOR	ANCHO	PESO
PULGADA		MM.		KG/M
.109	1	2.8	x 25.4	1.05
	1 1/4		x 31.7	1.33
	1 1/2		x 38.1	1.61
1/8	1 1/2	3.2	x 38.1	1.83
	1 3/4		x 44.4	2.14
	2		x 50.8	2.46
3/16	1 3/4	4.8	x 44.4	3.15
	2		x 50.8	3.63
	2 1/2		x 63.5	4.57
	3		x 76.2	5.52
1/4	1 3/4	6.3	x 44.4	4.12
	2		x 50.8	4.75
	2 1/2		x 63.5	6.10
	3		x 76.2	7.29
	3 1/2		x 88.9	8.63
	4		x 101.6	9.82
5/16	3	7.9	x 76.2	9.08
	3 1/2		x 88.9	10.71
	4		x 101.6	12.20
	5		x 127.0	15.32
	6		x 152.4	18.45
3/8	3	9.5	x 76.2	10.71
	3 1/2		x 88.9	12.64
	4		x 101.6	14.58
	5		x 127.0	18.30
	6		x 152.4	22.17
7/16	4	11.1	x 101.6	16.81
	6		x 152.4	25.59
1/2	3	12.7	x 76.2	13.99
	4		x 101.6	19.05
	5		x 127.0	24.11
	6		x 152.4	29.16
	8		x 203.2	39.28
9/16	8	14.3	x 203.2	44.05
5/8	4	15.9	x 101.6	23.36
	6		x 152.4	36.01
	8		x 203.2	48.66
3/4	6	19.0	x 152.4	42.71
	8		x 203.2	57.88
7/8	8	22.2	x 203.2	66.96
1	6	25.4	x 152.4	55.65
	8		x 203.2	75.89
1 1/8	8	28.6	x 203.2	84.67

ÁNGULOS (LADOS DESIGUALES)

Ángulos a 12.20 mts. (40 pies)

ESPESOR	ANCHO	ESPESOR	ANCHO	PESO
PULGADA		MM.		KG/M
3/16	x 3 x 2	4.8	x 76.2 x 50.8	4.57
1/4	x 3 x 2	6.3	x 76.2 x 50.8	6.10